



STANDARD FEATURES
POWDERCOATED CORROSION RESISTANT 2.5MM ALUMINIUM
HINGED DOOR WITH FIXED REAR PANEL OR HINGED FRONT AND REAR DOORS WITH GAS SPRINGS
100MM HIGH FRANGIBLE PLINTH
PASSIVE VENTILATION - VERMIN PROOF
EXTRUDED ALUMINIUM HINGES WITH STAINLESS STEEL PIN
ROOF SLOPED TO REAR FOR WATER RUN OFF
4 OFF VERTICAL RAILS
VANDAL RESISTANT LOCKS
DOCUMENT HOLDER
2.5MM ALUMINIUM MOUNTING PAN (NOT SHOWN)
INTERNAL HINGED ESCUTCHEON (NOT SHOWN)
SHELF TESTED TO 100KG (NOT SHOWN)
OPTIONAL DOUBLE SKIN WITH THERMAL INSULATION (AVAILABLE AS SPECIAL ORDER)

<b>UNLESS NOTED OTHERWISE:</b> 1. Dimensions in millimetres. 2. Deburr and break all sharp edges. Linear Dim's $\pm 0.5$ Hole Diameters $^{+0.1}_{-0.05}$ Angular Dim's $\pm 1^\circ$ All Bends $90^\circ \pm 0.5$		Logix Engineering Pty Ltd 28 Spine St, Sumner Park, QLD, 4074, Australia t: +61 434 034 703 w: www.logixeng.com.au e: tony@logixeng.com.au	Component Type <b>VIC ROADS APPROVED PA 030 251</b>
Linear tolerance C Angular tolerance C Geometry tolerance L	Finish <b>T33 SMOKE BLUE</b> Material <b>ALUMINIUM 2.5mm</b>		
Date Printed <b>30/10/2020</b> Date Created <b>25/07/2019</b>		Component / Assembly Description <b>ALUMINIUM ROADSIDE ENCLOSURE</b>	
Checked <b>RJS</b> Author <b>RJS</b> Mass <b>65 Kgs.</b>		Drawing Status <b>RELEASED FOR MANUFACTURE</b>	Drawing Type <b>RSE/VR/130704 1A</b>
Scale <b>1:20</b> Sheet No. <b>1 of 1</b> Sheet size <b>A3</b>	Drawing No. <b>RSE/VR/130704</b>	Drg Rev. <b>1A</b>	