



STANDARD FEATURES
POWDERCOATED CORROSION RESISTANT 2.5MM ALUMINIUM
HINGED DOOR WITH FIXED REAR PANEL OR HINGED FRONT AND REAR DOORS WITH GAS SPRINGS
100MM HIGH FRANGIBLE PLINTH
PASSIVE VENTILATION - VERMIN PROOF
EXTRUDED ALUMINIUM HINGES WITH STAINLESS STEEL PIN
ROOF SLOPED TO REAR FOR WATER RUN OFF
4 OFF VERTICAL RAILS
VANDAL RESISTANT LOCKS
DOCUMENT HOLDER
2.5MM ALUMINIUM MOUNTING PAN (NOT SHOWN)
INTERNAL HINGED ESCUTCHEON (NOT SHOWN)
SHELF TESTED TO 100KG (NOT SHOWN)

UNLESS NOTED OTHERWISE: 1. Dimensions in millimetres. 2. Deburr and break all sharp edges. Linear Dim's ± 0.5 Hole Diameters $^{+0.1}_{-0.05}$ Angular Dim's $\pm 1^\circ$ All Bends $90^\circ \pm 0.5$		Logix Engineering Pty Ltd 28 Spine St, Sumner Park, QLD, 4074, Australia t: +61 434 034 703 w: www.logixeng.com.au e: tony@logixeng.com.au	Component Type VIC ROADS APPROVED PA 030 251
Linear tolerance C Angular tolerance C Geometry tolerance L	Finish T33 SMOKE BLUE Material ALUMINIUM 2.5mm		
Date Printed 30/10/2020 Date Created 25/11/2019		Component / Assembly Description ALUMINIUM ROADSIDE ENCLOSURE	
Checked RJS Author RJS Mass 65 Kgs.		Drawing Status RELEASED FOR MANUFACTURE	Drawing Type RSE/VR/160704 1A
Scale 1:20 Sheet No. 1 of 1 Sheet size A3	Drawing No. RSE/VR/160704	Drg Rev. 1A	